

VIGOROUS W601



Rim Diameter	Factory Code	Tire Size	PR	LR	LI	SR	Rim	S.W.		O.D.		Max. Load				Max Pressure		Tread Depth		Weight		Stud Size TSMI	Road Condition	UTQG	Rolling Resistance	Wet Grip	Noise	
								in	mm	in	mm	Single		Dual		psi	kpa	32nd	mm	lbs	kg						db	Level
												lbs	kg	lbs	kg													
15"	300H7005	LT235/75R15	6	C	104/101	R	6.5J	9.3	236	28.9	734	1985	900	1820	825	50	350	16	13	33.8	15.3	13	M+S	-	E	D	73	B
16"	300H7006	LT225/75R16	10	E	115/112	S	6J	8.8	223	29.3	744	2680	1215	2470	1120	80	550	16	13	35.8	16.2	13	M+S	-	E	D	73	B
	300H7007	LT245/75R16	10	E	120/116	S	7J	9.8	248	30.5	774	3042	1380	2778	1260	80	550	16	13	41.6	18.9	13	M+S	-	E	D	73	B
	300H7008	LT265/75R16	10	E	123/120	R	7.5J	10.5	267	31.7	804	3415	1550	3085	1400	80	550	16	13	46.1	20.9	13	M+S	-	E	D	73	B
17"	300H7009	LT245/75R17	10	E	121/118	S	7J	9.8	248	31.5	800	3195	1450	2910	1320	80	550	16	13	43.2	19.6	13	M+S	-	E	D	73	B
	300H7002	LT245/70R17	10	E	119/116	S	7J	9.8	248.9	30.8	782.3	3000	1360.8	2755	1250	80	550	16	13	39.0	17.7	13	M+S	-	E	D	73	B
	300H7003	LT265/70R17	10	E	121/118	S	8J	10.7	272	31.7	804	3195	1450	2910	1320	80	550	16	13	43.9	19.9	13	M+S	-	E	D	73	B
18"	300H7004	LT275/70R18	10	E	125/122	S	8J	11.0	279.4	33.4	848.4	3640	1651.1	3305	1499.1	80	550	16	13	50.5	22.9	13	M+S	-	E	D	73	B
	300H7001	LT275/65R18	10	E	123/120	S	8J	11.0	279.4	32.1	815.3	3415	1880	3085	1400	80	550	16	13	47.3	21.4	13	M+S	-	E	D	73	B