

VIGOROUS MT601



Rim Diameter	Factory Code	Tire Size	PR	LR	LI	SR	Rim	S.W.		O.D.		Max. Load				Max Pressure		Tread Depth		Weight		Road Condition	UTQG	Rolling Resistance	Wet Grip	Noise	
								in	mm	in	mm	Single		Dual		psi	kpa	32nd	mm	lbs	kg					db	Level
										lbs	kg	lbs	kg														
15"	200H8001	31X10.50R15LT	6	C	109	Q	8.5J	10.6	268	30.7	781	2270	1030	-	-	50	350	18	14	42.8	19.4	M+S	-	-	-	-	-
	200H8006	33x12.50R15	6	C	108	Q	10J	12.6	318	32.8	832	2205	1000	-	-	35	250	19	15	55.8	25.3	M+S	-	-	-	-	-
16"	200H8002	LT235/75R15	6	C	104/101	Q	6.5J	9.3	235	29.1	739	1985	900	1820	825	50	350	18	14	37.4	17.0	M+S	-	-	-	-	-
	200H8003	LT245/75R16	10	E	120/116	Q	7J	9.8	248	30.7	780	3085	1400	2755	1250	80	550	18	14	44.9	20.4	M+S	-	-	-	-	-
17"	200H8005	LT265/75R16	10	E	123/120	Q	7.5J	10.5	267	31.9	810	3417	1550	3086	1400	80	550	18	14	50.4	22.9	M+S	-	-	-	-	-
	200H8004	LT265/70R17	10	E	121/118	Q	7J	10.7	272	31.9	810	3297	1495	2910	1320	80	550	18	14	50.7	23.0	M+S	-	-	-	-	-
20"	200H8007	33x12.50R20	10	E	114	Q	10J	12.6	318	32.8	832	2600	1180	-	-	65	450	22	16	57.7	26.2	M+S	-	-	-	-	-
	200H8008	35x12.50R20	10	E	121	Q	10J	12.6	318	34.8	883	3195	1450	-	-	65	450	22	16	62.8	28.5	M+S	-	-	-	-	-